

ME

4°C Blood Bank Refrigerator

Super High Quality Precise Temperature Control Safeguarding Security of Blood

XC - 368L

Constant Temperature under Intelligent Control

Return air duct design, ensuring a temperature control accuracy at 0.1°C inside the cabinet;
High-precision computerized temperature control system, built-in sensors for upper/lower zone temperature, ambient temperature, evaporator temperature, and operation control, ensuring safe and stable operation.

Security System

Perfect audible and visual alarm system comes with alarm functions for high temperature, low temperature, sensor fault, door opening, and power failure.

🔯 High-efficiency Refrigeration

• Advanced air cooling design, precision temperature control, safeguarding security of blood • Stainless steel inner container, copper tube evaporator, powerful refrigeration





Precise Temperature Control

1-inch high-brightness digital temperature display, allowing to set the temperature precision of $\pm 1^\circ\mathrm{C}$ inside the cabinet, and the precision of temperature display accuracy at 0.1°C



Refrigeration System

· Equipped with brand high-efficient compressor, EBM fan motor, performing efficient energy and quiet. · High-precision computerized temperature control system, built-in sensors for upper/lower zone temperature, ambient temperature, evaporator temperature, and operation control, ensuring safe and stable operation.




DC/DC Power Management

- · Equipped with DC/DC power management module, optimized energy saving;
- · High-precision voltage control, stabilizing the voltage and refrigerator performance
- · Reduce the redundancy heat, completely eradicate overheating risk

Scope of Application

Suitable for use in blood banks, hospitals, health and disease prevention systems, research institutions, colleges & universities, the electronic industry, biological engineering, laboratories in colleges & universities, military enterprises, deep-sea fishing companies, etc.

Performance Data / Cooling Curve



6

🗠 External Dimensions







Automatic Defrost

· Return air duct design, ensuring a temperature control precision within 2~6°C inside the cabinet; Equipped with automatic defrost function, force defrost



Alam System

· Perfect audible and visual alarm system comes with alarm function for high temperature, low temperature, sensor fault, door open, and power off.



Human-oriented

· Equipped with 5 dip-coating shelves with label strips

· 20 dip-coating blood bag frames (optional stainless steel frame), can hold 220 blood bags in 450ml for each.

Specification Chart

4°C Blood Bank Refrigerator	
Model	XC-368L
Cabinet Type	Upright
Capacity(L)	368
Internal Size(W*D*H)mm	677*493*1145
External Size(W*D*H)mm	806*723*1870
Package Size(W*D*H)mm	808*908*2046
NW/GW(Kgs)	163/193
Performance	
Temperature Setting	2~6°C
Ambient Temperature	16-32°C
Climate Class	Ν
Controller	Microprocessor
Display	Digital display
Refrigeration	
Compressor	1pc
Cooling Method	Air cooling
Defrost Mode	Automatic
Refrigerant	R134a
Insulation Thickness(mm)	R/L/U/B:54,D:55
Construction	
External Material	Cold rolled steel sheet
Inner Material	Stainless steel
Shelves	5(coated steel wired shelf)
Door Lock with Key	Yes
Blood Basket	20
Access Port	1pc. Ø 25 mm
Casters	4 (2 casters with brake)
Data Logging/Interval/Recording Time	USB/Record every 10 minutes / 2 years
Backup Battery	Yes
Alarm	
Temperature	High/Low temperature,High ambient temperature
Electrical	Power failure , Low battery
System	Sensor failure,Door ajar,Condenser overheating,Built-in USB datalogger failure
Electrical	
Power Supply(V/HZ)	220/50
Rated Power(W)	420
Input Power(W)	528
Power Consumption(KWh/24h)	3.56
Rated Current(A)	2.4
Accessories	
Standard	Printer, RS485, Remote alarm contact

*The model, parameters and performance specified in this brochure may be changed without prior notice because of product upgrading. *There may be differences between the product images shown in this brochure and the actual products. When you are buying any product, please check the actual product.

